


Pre-Crash-Matrix (PCM)

Format Specification v5.0

Effective 30.09.2021



Contact VUFO
(Institute for Traffic Accident Research
at Dresden University of Technology)

Mail pcm@vufo.de

Address Semperstraße 2a
01069 Dresden - Germany

Table of Contents

Table of Contents	2
Legal Framework.....	3
Preface – What is PCM?	4
Description of tables and variables	5
Global data.....	6
Table: global_data	6
Road users.....	7
Table: participant_data	7
Table: participant_shape.....	9
Table: dynamics.....	12
Table: intended_course	14
Environment.....	15
Table: road_marks.....	15
Table: standard_road_marks.....	16
Table: objects	17
Table: standard_objects	19
Table: traffic_signs	20
Table: standard_traffic_signs.....	21
Properties and Libraries	22
Table: property_DE_road_marks.....	22
Table: library_DE_standard_road_marks	23
Table: library_DE_standard_objects.....	24
Table: library_DE_standard_traffic_signs	25
Appendix A: Advices for positioning objects	26
Appendix B: List of object types (OBJTYPES).....	27
Table: property_DE_road_marks.....	27
Table: library_DE_standard_road_marks	30
Table: library_DE_standard_objects.....	36
Table: library_DE_standard_traffic_signs	40

Legal Framework

GENERAL

All trade names, trademarks and/or company logos referenced in this document belong to their respective companies.

VUFO GmbH (VUFO) is the owner of all intellectual property rights in this document including but not limited to, copyrights to this document.

The PCM format as well as this document will be improved by VUFO in the future. Changes to the PCM format can be made by VUFO at any time with no official notice. It is planned to incorporate changes in this document and publish new editions periodically. No part of this document may be reproduced, in whole or in part, in any way, including, but not limited to, photocopy, photograph, or other record, without the prior written permission of VUFO.

WARRANTY

The PCM format specifications are provided by VUFO “as is”, without any warranty, either express or implied, including (but not limited to) any warranties or conditions of title, non-infringement, merchantability or fitness for a particular purpose. All warranties are expressly and specifically disclaimed.

DISCLAIMER OF LIABILITY

VUFO is not responsible for any direct, indirect, incidental, special, exemplary, consequential damages (including without limitation of lost profits) arising from the use of this document, the provided database and example cases.

The document may contain inaccuracies or typographical errors.

PUBLIC LICENSE STATEMENT

The PCM format is property of VUFO GmbH (VUFO) and protected under the copyright law of the Federal Republic of Germany. Users should name VUFO as owner of the PCM format in publications that refer to the PCM.

VUFO grants all users a non-exclusive and non-transferable right to use the format as follows:

- I. Storing data in a PCM database created according to the format specifications
- II. Accessing data stored in a PCM database
- III. Exchanging data in the PCM format with other stakeholders

Any attempt to sub-license, transfer or assign all or any part of the PCM format specification is prohibited.

©2011-2019 VUFO GmbH

Preface – What is PCM?

WHAT IS PCM?

PCM is the abbreviation for Pre-Crash-Matrix, and is a specified format to describe the phase of a traffic accident prior to the collision (the so-called pre-crash phase). It describes participants, its dynamics as well as the environment.

Initially the VUFO (Institute for Traffic Accident Research at Dresden University of Technology) developed the format in 2011 to provide pre-crash data for accidents investigated within the German In-Depth Accident Study (GIDAS). In January 2019, the format was defined in a more general way. Since then, it is applicable for any accident or scenario database and publicly accessible.

As it does not describe further data regarding the accident / scenario (e.g. accident description, accident type, injury severities, et al.), specific analyses should always refer to the linked accident / scenario database.

PCM STRUCTURE

Figure 1 shows the PCM structure including all tables in their hierarchic definitions. Attached to some environment tables there are property tables (containing meta data) and library tables which refer to country-specific definitions. The completion as well as the extension on other country-specific libraries is possible and one of the intended objectives for the future PCM development process.

CREATION AND SPECIFIC PCM DATABASE

A PCM case can be created by simulation methods (e.g. accident reconstruction) as well as data recording (e.g. from Event Data Recorders (EDR), Naturalistic Driving Study (NDS), Field Operational Test (FOT), ...). The resulting database contains a set of accidents / scenarios in PCM format.

The standard file format is a Microsoft Access database (mdb). As there exists the 2GB limit on a 32-bit operating system an alternative will be discussed for a future format release.

The name of the resulting PCM database should always refer to the linked database, e.g. "GIDAS-PCM".

EXAMPLE CASE

An example case is available for download on our website <https://www.vufo.de/>.

FURTHER DEVELOPEMENT

PCM is a "living format" that will evolve in cooperation with their users and partners. Send suggestions for format extensions, new or missing objects (OBJTYPE), mistakes in the specification and especially further libraries (e.g. with your countries specific characteristics) directly to VUFO via pcm@vufo.de. In order to provide uniform definitions for all users the extensions can then be included in the next release.

Description of tables and variables

The following chapters describe the variables in the respective tables as well as their unit and data type. In general, if any information is unknown use the value 99999.

The following abbreviations are used:

- COS – Coordinate system (3-dimensional, cartesian)
- COG – Center Of Gravity
- GPS – Global Positioning System (according to WGS 84)




Figure 1: Hierarchical structure of PCM

Global data

Table: global_data

Description: The table global_data provides general information about the accident / scenario.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
DATETIME	Date and time expressed according to ISO 8601:2004 This represents the global zero for all TIME values. Unknown digits may be omitted or expressed by "9" Example: 2019-01-31T11:11:11.111+00:00	[]	Short text
PARTICIP	Number of involved participants	[]	Long int.
SOLVER	Used solver for vehicle dynamics 1 – IPG CarMaker 2 – DSD PC-Crash 3 – AnalyzerPro 4 – Virtual Crash 5 – IPG TruckMaker 6 – IPG MotorcycleMaker 7 – Mechanical Simulation™ CarSim® 8 – Mechanical Simulation™ TruckSim® 9 – Mechanical Simulation™ BikeSim® 10 – Tass International PreScan 11 – dSPACE Automotive Simulation Models (ASM) 12 – TESIS DYNA4 13 – Pro Impact 88888 – other	[]	Long int.
GPSLAT	GPS latitude of global COS according to WGS 84 (decimal, e.g. 51.034186)	[°]	Double
GPSLON	GPS longitude of global COS according to WGS 84 (decimal, e.g. 13.744801)	[°]	Double
GPSELE	Elevation of global COS according to WGS84 reference system (ellipsoidal height)	[m]	Double

Road users

Table: participant_data

Description: The table participant_data contains relevant variables to parametrise participants. This data can be used to model the geometry and further attributes. The variable PARTID is the participant identifier. Consider the table participant_shape to model the participant geometry in detail. The variable PARTTYPE describes the type of road user.

It is recommended to use a local reference COS according to ISO 8855 with the COG as origin.




Figure 2: participant definitions

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
PARTID	Participant identifier per CASEID	[]	Long int.
PARTTYPE	Participant type: 0 – passenger car 1 – pedestrian 2 – motorbike 3 – bicycle 4 – truck 5 – bus 6 – tram/train 7 – trailer 8 – camper 9 – agricultural vehicle 10 – construction vehicle	[]	Long int.

	11 – emergency vehicle 12 – large animal 13 – small animal 88888 – other		
LENGTH	Length	[m]	Double
WIDTH	Width	[m]	Double
HEIGHT	Height	[m]	Double
TRACKWIDTH	Track width	[m]	Double
WHEELBASE	Wheelbase	[m]	Double
FRONTAXLEX	Position of front axle in x-direction in reference to participant local coordinate system (participant shape)	[m]	Double
WEIGHT	Weight	[kg]	Double
COGX	x-coordinate of COG in reference to participant local coordinate system (participant shape)	[m]	Double
COGY	y-coordinate of COG in reference to participant local coordinate system (participant shape)	[m]	Double
COGZ	z-coordinate of COG in reference to participant local coordinate system (participant shape)	[m]	Double
IXX	Moment of inertia around x-axis in reference to COG	[kgm ²]	Double
IYY	Moment of inertia around y-axis in reference to COG	[kgm ²]	Double
IZZ	Moment of inertia around z-axis in reference to COG	[kgm ²]	Double

Table: participant_shape

Description: The table participant_shape defines the geometrical shape for each participant by surfaces. Each surface contour is defined by points. Each point is defined by its position $(x \ y \ z)^T$ in reference to the participants local COS.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
PARTID	Participant identifier per CASEID	[]	Long int.
SURFID	Surface identifier per PARTID	[]	Long int.
POINTID	Point identifier per SURFID	[]	Long int.
X	Local x-coordinate	[m]	Double
Y	Local y-coordinate	[m]	Double
Z	Local z-coordinate	[m]	Double

Examples for participant shapes:




Figure 3: Example for 2D vehicle shape definition of a passenger car




Figure 4: Example for 3D vehicle shape definition of a passenger car




Figure 5: Example for 2D vehicle shape definition of a motorcycle/ bicycle




Figure 6: Example for 3D vehicle shape definition of a motorcycle/ bicycle



Figure 7: Example for 2D pedestrian shape definition




Figure 8: Example for 3D pedestrian shape definition

Table: dynamics

Description: The table dynamics defines the global position of participants $(x \ y \ z \ \Phi \ \Theta \ \Psi)^T$ according to the global COS as well as velocity and acceleration of the participants COG according to the local COS at each time step of the simulation (see Figure 9).




Figure 9: Global (red) and local (black) coordinate systems

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
PARTID	Participant identifier per CASEID	[]	Long int.
VARIATIONID	Variation identifier per PARTID 0 – original accident / scenario ≥ 1 – simulation variation, like additional braking or other	[]	Long int.
TIME	Time step	[s]	Double
POSX	Global x-position of COG	[m]	Double
POSY	Global y-position of COG	[m]	Double
POSZ	Global z-position of COG	[m]	Double
POSPHI	Global roll angle Φ of COG (cardan angles)	[rad]	Double
POSTHETA	Global pitch angle Θ of COG (cardan angles)	[rad]	Double
POSPSI	Global yaw angle Ψ of COG (cardan angles)	[rad]	Double
VX	Velocity of COG in local x-direction	[m/s]	Double
VY	Velocity of COG in local y-direction	[m/s]	Double

VZ	Velocity of COG in local z-direction	[m/s]	Double
AX	Acceleration of COG in local x-direction	[m/s ²]	Double
AY	Acceleration of COG in local y-direction	[m/s ²]	Double
AZ	Acceleration of COG in local z-direction	[m/s ²]	Double
MUE	Coefficient of friction	[]	Double
REC	Reconstruction / data recording availability for the given time step 1 – Values based on reconstruction / data recording 0 – Values based on extension of reconstruction / data recording	[]	Long int.

Table: intended_course

Description: The table intended_course defines the course the participant initially intended to follow. The POINTID determines the points with their global position $(x \ y \ z)^T$.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
PARTID	Participant identifier per CASEID	[]	Long int.
VARIATIONID	Variation identifier per PARTID 0 – original accident / scenario ≥ 1 – variation	[]	Long int.
POINTID	Point identifier per VARIATIONID	[]	Long int.
POSX	Global x-coordinate	[m]	Double
POSY	Global y-coordinate	[m]	Double
POSZ	Global z-coordinate	[m]	Double

Environment

Several tables and their link to a respective library or property describe the accident / scenario's environment.

Table: road_marks

Description: The table road_marks is part of the environment description. It defines the relevant boundaries and markings of the road as objects, each with an OBJID as identifier and consisting of points with their position $(x \ y \ z)^T$ in reference to global COS. These are no 3D objects, but they can be positioned in 3D.

The variable OBJTYPE defines the kind of road boundary or marking. The list of possible OBJTYPEs and their definition is given in the table property_DE_road_marks (example for Germany).

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
OBJID	Object identifier per CASEID	[]	Long int.
POINTID	Point identifier per OBJID	[]	Long int.
OBJTYPE	Type of object	[]	Long int.
X	Global x-coordinate	[m]	Double
Y	Global y-coordinate	[m]	Double
Z	Global z-coordinate	[m]	Double

Table: standard_road_marks

Description: The table standard_road_marks is part of the environment description. It defines frequently existing road markings (e.g. turning arrow, bicycle path, "BUS" symbol) each with an OBJID as identifier. The advantage of standard road marks is that they are defined only once and can be used for multiple cases, which saves storage space in the database.

The variable OBJTYPE defines the kind of road mark. The list of possible OBJTYPES and their definition is given in the table library_DE_standard_road_marks (example for Germany).

These are no 3D objects, but can be positioned and scaled in 3D to global COS through its reference point and the scaling factors. See also Appendix A: Advices for positioning objects.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
OBJID	Object identifier per CASEID	[]	Long int.
OBJTYPE	Type of object	[]	Long int.
REFX	Global x-coordinate of reference point	[m]	Double
REFY	Global y-coordinate of reference point	[m]	Double
REFZ	Global z-coordinate of reference point	[m]	Double
REFROTX	Rotation angle around x-axis at reference point (cardan angles)	[rad]	Double
REFROTY	Rotation angle around y-axis at reference point (cardan angles)	[rad]	Double
REFROTZ	Rotation angle around z-axis at reference point (cardan angles)	[rad]	Double
SCALEX	Scaling factor in x-direction at reference point	[]	Double
SCALEY	Scaling factor in y-direction at reference point	[]	Double
SCALEZ	Scaling factor in z-direction at reference point	[]	Double

Table: objects

Description: The table is part of the environment description. It defines the geometrical shape of relevant stationary objects by surfaces. Each surface contour is defined by points. Each point is defined by its position $(x \ y \ z)^T$ in reference to global COS.

The variable OBJTYPE defines the kind of object. The list of possible OBJTYPES is given in the table below.

Comments: In order to provide a uniform table for all users, it is recommended to forward extensions to pcm@vufo.de. The extensions can then be included in a new release.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
OBJID	Object identifier per CASEID	[]	Long int.
SURFID	Surface identifier per OBJID	[]	Long int.
POINTID	Point identifier per SURFID	[]	Long int.
OBJTYPE	Type of object	[]	Long int.
X	Global x-coordinate	[m]	Double
Y	Global y-coordinate	[m]	Double
Z	Global z-coordinate	[m]	Double

List of OBJTYPES:

OBJTYPE	Description
520	Traffic barrier (steel)
521	Traffic barrier (concrete)
522	Traffic barrier (not specified)
523	Traffic pole for guidance, warning and barriers
524	House wall, bridge pier
525	Game fence, wooden fence
526	Bush, hedge
527	Railing
528	Group of trees
529	Railway gate
530	Traffic cone

531	Bus Stop
532	Taxi rank
533	Speed bump
534	Bridge
535	Tunnel
536	Garbage bin / waste basket
537	Earth wall
538	Embankment
549	Other areal objects
599	Objects – not specified

Table: standard_objects

Description: The table standard_objects is part of the environment description. It defines frequently existing stationary objects (e.g. trees, parking vehicles), each with an OBJID as identifier. The advantage of standard objects is that they are defined only once and can be used for multiple cases, which saves storage space in the database.

The variable OBJTYPE defines the kind of object. The list of possible OBJTYPES and their definition is given in the table library_DE_standard_objects (example for Germany).

Each object can be positioned and scaled in 3D to global COS through its reference point and the scaling factors. See also Appendix A: Advices for positioning objects.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
OBJID	Object identifier per CASEID	[]	Long int.
OBJTYPE	Type of object	[]	Long int.
REFX	Global x-Coordinate of reference point	[m]	Double
REFY	Global y-Coordinate of reference point	[m]	Double
REFZ	Global z-Coordinate of reference point	[m]	Double
REFROTX	Global rotation angle around x-axis at reference point (cardan angles)	[rad]	Double
REFROTY	Global rotation angle around y-axis at reference point (cardan angles)	[rad]	Double
REFROTZ	Global rotation angle around z-axis at reference point (cardan angles)	[rad]	Double
SCALEX	Scaling factor in x-direction at reference point	[]	Double
SCALEY	Scaling factor in y-direction at reference point	[]	Double
SCALEZ	Scaling factor in z-direction at reference point	[]	Double

Table: traffic_signs

Description: The table traffic_signs is part of the environment description. It defines the geometrical shape of arbitrary traffic signs by surfaces (be aware of standard traffic signs). Each surface contour is defined by points. Each point is defined by its position $(x \ y \ z)^T$ in reference to global COS.

The variable OBJTYPE defines the kind of object. There is currently no list of possible OBJTYPES beyond the library_DE_standard_traffic_signs.

Comments: In order to provide a uniform table for all users, it is recommended to forward extensions to pcm@vufo.de. The extensions can then be included in a new release.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
OBJID	Object identifier per CASEID	[]	Long int.
SURFID	Surface identifier per OBJID	[]	Long int.
POINTID	Point identifier per SURFID	[]	Long int.
OBJTYPE	Type of object	[]	Long int.
X	Global x-coordinate	[m]	Double
Y	Global y-coordinate	[m]	Double
Z	Global z-coordinate	[m]	Double

Table: standard_traffic_signs

Description: The table standard_traffic_signs is part of the environment description. It defines frequently existing traffic signs, each with an OBJID as identifier. The advantage of standard traffic signs is that they are defined only once and can be used for multiple cases, which saves storage space in the database.

The variable OBJTYPE defines the kind of object. The list of possible OBJTYPES and their definition is given in the table library_DE_standard_traffic_signs (example for Germany).

Each object can be positioned and scaled in 3D to global COS through its reference point and the scaling factors. See also Appendix A: Advices for positioning objects.

Variable	Description	Unit	Type
CASEID	Unique case identifier	[]	Short text
OBJID	Object identifier per CASEID	[]	Long int.
OBJTYPE	Type of object	[]	Long int.
REFX	Global x-coordinate of reference point	[m]	Double
REFY	Global y-coordinate of reference point	[m]	Double
REFZ	Global z-coordinate of reference point	[m]	Double
REFROTX	Rotation angle around x-axis at reference point (cardan angles)	[rad]	Double
REFROTY	Rotation angle around y-axis at reference point (cardan angles)	[rad]	Double
REFROTZ	Rotation angle around z-axis at reference point (cardan angles)	[rad]	Double
SCALEX	Scaling factor in x-direction at reference point	[]	Double
SCALEY	Scaling factor in y-direction at reference point	[]	Double
SCALEZ	Scaling factor in z-direction at reference point	[]	Double

Properties and Libraries

Table: property_DE_road_marks

Description: The table property_DE_road_marks is referred to by table road_marks through OBJTYPE. It defines the width, length and gap of a line and can be used to visualize the various road boundaries and markings.

Comments: Countries-specific road boundaries and markings may be required. Additional properties can be added for this purpose. The format of the library must remain the same. The name of the library should be changed according to the ISO3166 Alpha-2 code.

Example:

Germany: "property_DE_road_marks"

China: "property_CN_road_marks"

...

In order to provide a uniform table for all users, it is recommended to forward extensions to pcm@vufo.de. The extensions can then be included in a new release.

Variable	Description	Unit	Type
OBJTYPE	Type of object	[]	Long int.
DESCRIPTION	Description object	[]	Short text
WIDTH	Width of the line	[m]	Double
LENGTH	Length of line	[m]	Double
GAP	Length of gap	[m]	Double




Figure 10: Examples for road marks

Table: library_DE_standard_road_marks

Description: The table library_DE_standard_road_marks defines the general shape of standard road marks (e.g. turning arrow, bicycle path, "BUS" symbol) in Germany and is referred to by standard_road_marks through OBJTYPE.

The variable OBJTYPE defines the kind of road mark. The list of possible OBJTYPEs is given in the table below (for Germany). Each OBJTYPE consists of one or several surfaces, each consisting of points with their position $(x \ y \ z)^T$ in reference to local COS (always SURFID = 1, POINTID = 1).

These are no 3D objects, but can be positioned and scaled in 3D to global COS through its reference point and the scaling factors. See also Appendix A: Advices for positioning objects.

Comments: Countries-specific standard road marks may be required. Additional libraries can be added for this purpose. The format of the library must remain the same. The name of the library should be changed according to the ISO3166 Alpha-2 code,

Example:

Germany: "library_DE_standard_road_marks"

China: "library_CN_standard_road_marks"

...

In order to provide a uniform table for all users, it is recommended to forward extensions to pcm@vufo.de. The extensions can then be included in a new release.

Variable	Description	Unit	Type
OBJTYPE	Type of object	[]	Long int.
SURFID	Surface identifier per OBJTYPE	[]	Long int.
POINTID	Point identifier per SURFID	[]	Long int.
X	Local x-coordinate	[m]	Double
Y	Local y-coordinate	[m]	Double
Z	Local z-coordinate	[m]	Double

Table: library_DE_standard_objects

Description: The table library_DE_standard_objects defines the general shape of frequently existing stationary objects in Germany (e.g. trees, parking vehicles) and is referred to by standard_objects through OBJTYPE.

The variable OBJTYPE defines the kind of road mark. The list of possible OBJTYPEs is given in the table below (for Germany). Each OBJTYPE consists of one or several surfaces, each consisting of points with their position $(x \ y \ z)^T$ in reference to local COS (always SURFID = 1, POINTID = 1).

They can be positioned and scaled in 3D in reference to global COS through its reference point and the scaling factors. See also Appendix A: Advices for positioning objects.

Comments: Countries-specific standard road marks may be required. Additional libraries can be added for this purpose. The format of the library must remain the same. The name of the library should be changed according to the ISO3166 Alpha-2 code,

Example:

Germany: "library_DE_standard_objects"

China: "library_CN_standard_objects"

...

In order to provide a uniform table for all users, it is recommended to forward extensions to pcm@vufo.de. The extensions can then be included in a new release.

Variable	Description	Unit	Type
OBJTYPE	Type of object	[]	Long int.
SURFID	Surface identifier per OBJTYPE	[]	Long int.
POINTID	Point identifier per SURFID	[]	Long int.
X	Local x-coordinate	[m]	Double
Y	Local y-coordinate	[m]	Double
Z	Local z-coordinate	[m]	Double

Table: library_DE_standard_traffic_signs

Description: The table library_DE_standard_traffic_signs defines the general shape of frequently existing traffic signs in Germany and is referred to by standard_traffic_signs through OBJTYPE.

The variable OBJTYPE defines the kind of road mark. The list of possible OBJTYPEs is given in the table below (for Germany). Each OBJTYPE consists of one or several surfaces, each consisting of points with their position $(x \ y \ z)^T$ in reference to local COS (always SURFID = 1, POINTID = 1).

They can be positioned and scaled in 3D in reference to global COS through its reference point and the scaling factors. See also Appendix A: Advices for positioning objects.

Comments: Countries-specific standard road marks may be required. Additional libraries can be added for this purpose. The format of the library must remain the same. The name of the library should be changed according to the ISO3166 Alpha-2 code,

Example:

Germany: "library_DE_standard_traffic_signs"

China: "library_CN_standard_traffic_signs"

...

In order to provide a uniform table for all users, it is recommended to forward extensions to pcm@vufo.de. The extensions can then be included in a new release.

Variable	Description	Unit	Type
OBJTYPE	Type of object	[]	Long int.
SURFID	Surface identifier per OBJTYPE	[]	Long int.
POINTID	Point identifier per SURFID	[]	Long int.
X	Local x-coordinate	[m]	Double
Y	Local y-coordinate	[m]	Double
Z	Local z-coordinate	[m]	Double

Appendix A: Advices for positioning objects

SCALING

- Take x-, y-, and z-coordinates from library for concerning OBJID (e.g. library_DE_standard_objects) and multiply by scaling factor 'SCALEX', 'SCALEY', 'SCALEZ':

$$x_{sijk} = SCALEX_i \cdot x_{ijk} ,$$

$$y_{sijk} = SCALEY_i \cdot y_{ijk} ,$$

$$z_{sijk} = SCALEZ_i \cdot z_{ijk} ,$$

for all $i \in OBJID$, $j \in SURFNO$, $k \in POINTNO$

ROTATION

- Define matrix R_x for rotation around the x-axis by 'REFROTX':

$$R_x(\alpha_i) = \begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos \alpha_i & -\sin \alpha_i \\ 0 & \sin \alpha_i & \cos \alpha_i \end{pmatrix} , \text{ where } \alpha_i = \text{REFROTX}_i$$

- Define matrix R_y for rotation around the y-axis by 'REFROTY':

$$R_y(\beta_i) = \begin{pmatrix} \cos \beta_i & 0 & \sin \beta_i \\ 0 & 1 & 0 \\ -\sin \beta_i & 0 & \cos \beta_i \end{pmatrix} , \text{ where } \beta_i = \text{REFROTY}_i$$

- Define matrix R_z for rotation around the z-axis by 'REFROTZ':

$$R_z(\gamma_i) = \begin{pmatrix} \cos \gamma_i & -\sin \gamma_i & 0 \\ \sin \gamma_i & \cos \gamma_i & 0 \\ 0 & 0 & 1 \end{pmatrix} , \text{ where } \gamma_i = \text{REFROTZ}_i$$

The rotation is composed of the rotation matrices multiplied by the x-, y-, z-coordinates.

$$\left(x_{rijk}, y_{rijk}, z_{rijk} \right)^T = R_z(\gamma_i) \cdot R_y(\beta_i) \cdot R_x(\alpha_i) \cdot \left(x_{sijk}, y_{sijk}, z_{sijk} \right)^T$$

for all $i \in OBJID$, $j \in SURFNO$, $k \in POINTNO$

TRANSLATION

- Translate x-, y-, z-coordinates by vector ('REFX', 'REFY', 'REFZ'):

$$\left(x_{tijk}, y_{tijk}, z_{tijk} \right) = \left(x_{rijk}, y_{rijk}, z_{rijk} \right) + \left(x_{ref_i}, y_{ref_i}, z_{ref_i} \right) ,$$

for all $i \in OBJID$, $j \in SURFNO$, $k \in POINTNO$

Appendix B: List of object types (OBJTYPES)

Table: property_DE_road_marks

List of OBJTYPE:





OBJTYPE	DESCRIPTION	WIDTH	LENGTH	GAP
<i>General</i>				
101	Roadside (e.g. curb)	-	-	-
102	Continuous to indicate stopping restriction (e.g. zigzag pattern)	0.12	-	-
103	Continuous for barred areas	0.5	-	-
104	Continuous for cyclists	0.25	-	-
105	Interrupted for cyclists	0.25	1	2
106	Interrupted for cyclists	0.25	0.5	0.5
107	Lateral, interrupted for cyclists	0.25	0.5	0.2
108	Lateral, continuous for stopping traffic (e.g. at stop signs, traffic lights, railway crossing signs)	0.5	-	-
109	Lateral, interrupted for turning events	0.5	0.5	0.25
110	Lateral, interrupted for pedestrians (e.g. at traffic lights)	0.12	0.5	0.2
111	Lateral, interrupted for pedestrians (crosswalk)	3	0.5	0.5
112	Railway tracks	-	-	-
114	Parking lot	-	-	-
115	Interrupted for cyclists	0.12	1	1
116	Lane Marking without white marking (e.g. with stones for parking spaces or bus stops)	-	-	-
196	Former marks continuous	-	-	-
197	Former marks of the road edge	-	-	-
198	Former marks interrupted short	-	-	-
199	Former marks interrupted long	-	-	-
<i>Urban</i>				
201	Continuous road edge	0.25	-	-
202	Interrupted road edge (no junction)	0.25	1	0.5





203	Interrupted road edge (junction area)	0.25	3	3
204	Interrupted road edge (close to junction area)	0.25	1.5	1.5
205	Continuous lane marking	0.12	-	-
206	Guiding marks (no junction)	0.12	3	6
207	Guiding marks (in general)	0.12	3	1.5
208	Guiding marks (junction area)	0.12	3	3
209	Interrupted road edge (junction area)	0.12	1.5	1.5
<i>Extra urban</i>				
221	Continuous road edge	0.25	-	-
222	Interrupted road edge (junction area)	0.25	3	3
223	Interrupted road edge (close to junction area)	0.25	1.5	1.5
224	Continuous lane marking	0.12	-	-
225	Guiding marks (no junction)	0.12	4	8
226	Guiding marks (in general)	0.12	4	2
227	Guiding marks (junction area)	0.12	3	3
<i>Motorway</i>				
241	Continuous road edge	0.3	-	-
242	Interrupted road edge (junction area)	0.3	6	6
243	Continuous lane marking	0.15	-	-
244	Guiding marks (no junction)	0.15	6	12
245	Guiding marks (in general)	0.15	6	3
246	Guiding marks (connecting ramp, adjunct lane)	0.15	6	6
<i>Construction site</i>				
261	Continuous road edge	0.25	-	-
262	Interrupted road edge (close to junction) – urban	0.25	1.5	1.5
263	Interrupted road edge (junction area) – extra urban	0.25	3	3
264	Interrupted road edge (junction area) – motorway	0.3	6	6
265	Guiding marks (no junction) – urban	0.12	3	6
266	Guiding marks (junction area) – urban	0.12	3	3






267	Guiding marks (no junction) – extra urban	0.12	4	8
268	Guiding marks (no junction) – motorway	0.15	6	12
269	Interrupted marks for bicycle / pedestrian passage	0.25	0.5	0.2
270	Lateral, continuous for stopping traffic (e.g. at stop signs, traffic lights, railway crossing signs)	0.5	-	-
271	not specified	-	-	-
<i>Roadside</i>				
401	Pavement	-	-	-
402	Bicycle path	-	-	-
405	Combined bicycle pedestrian path	-	-	-




Table: library_DE_standard_road_marks






List of OBJTYPE:

OBJTYPE	Description	Pictogram
301	Arrow to turn left	
302	Arrow to turn right	
303	Arrow to turn left and right	
304	Arrow to go straight	

305	Arrow to go straight and to turn left and right	
306	Arrow to go straight and turn left	
307	Arrow to go straight and turn right	
308	Preliminary arrow to turn left	
309	Preliminary arrow to turn right	
310	Pictogram velocity 20	

311	Pictogram velocity 30	
312	Pictogram velocity 50	
313	Pictogram bikeway 1	
314	Pictogram bikeway 2	
315	Pictogram wheelchair	
316	Pictogram STOP	

<p>317</p>	<p>Pictogram BUS 1</p>	
<p>318</p>	<p>Pictogram BUS 2</p>	
<p>319</p>	<p>Pictogram BUS 3</p>	

320	Bicycle arrow to turn left	 <p>A 2D coordinate system with x and y axes ranging from -1.5 to 1.5. A red arrow starts at the origin (0,0) and points downwards to y = -0.5. From there, it curves to the left, ending with a hook pointing towards the upper-left quadrant.</p>
321	Bicycle arrow to turn right	 <p>A 2D coordinate system with x and y axes ranging from -1.5 to 1.5. A red arrow starts at the origin (0,0) and points downwards to y = -0.5. From there, it curves to the right, ending with a hook pointing towards the upper-right quadrant.</p>
322	Bicycle arrow to turn left and right	 <p>A 2D coordinate system with x and y axes ranging from -1.5 to 1.5. A red arrow starts at the origin (0,0) and points downwards to y = -0.5. From there, it splits into two symmetrical hooks, one pointing towards the upper-left and the other towards the upper-right.</p>
323	Bicycle arrow to go straight	 <p>A 2D coordinate system with x and y axes ranging from -1.5 to 1.5. A red arrow starts at the origin (0,0) and points straight upwards to y = 0.5.</p>
324	Bicycle arrow to go straight and to turn left and right	 <p>A 2D coordinate system with x and y axes ranging from -1.5 to 1.5. A red arrow starts at the origin (0,0) and points straight upwards to y = 0.5. From the tip of this arrow, it splits into two symmetrical hooks, one pointing towards the upper-left and the other towards the upper-right.</p>


















325	Bicycle arrow to go straight and turn left	
326	Bicycle arrow to go straight and turn right	
327	Arrow to turn around	

Table: library_DE_standard_objects

List of OBJTYPE:

OBJTYPE	Description	Pictogram
501	Tree trunk (w/o crown)	
502	Pole of wood, concrete or steel	
503	Reflector post	
519	Other round objects	

550	Standing motorcycle	
551	Standing passenger car - small	
552	Standing passenger car - medium	
553	Standing passenger car - large	
554	Standing transporter	

555	Standing trailer	 <p>A 3D plot showing a red rectangular prism representing a standing trailer. The x-axis ranges from -5 to 5, the y-axis from -1 to 1, and the z-axis from 0 to 4. The prism is centered at the origin (0,0,0) and has a height of 4 meters.</p>
556	Standing bus	 <p>A 3D plot showing a red rectangular prism representing a standing bus. The x-axis ranges from -10 to 10, the y-axis from -1 to 1, and the z-axis from 0 to 4. The prism is centered at the origin (0,0,0) and has a height of 4 meters.</p>
557	Standing truck	 <p>A 3D plot showing a red rectangular prism representing a standing truck. The x-axis ranges from -10 to 10, the y-axis from -1 to 1, and the z-axis from 0 to 4. The prism is centered at the origin (0,0,0) and has a height of 4 meters.</p>
558	Standing truck trailer	 <p>A 3D plot showing a red rectangular prism representing a standing truck trailer. The x-axis ranges from -5 to 5, the y-axis from -1 to 1, and the z-axis from 0 to 4. The prism is centered at the origin (0,0,0) and has a height of 4 meters.</p>
559	Standing tram Dresden	 <p>A 3D plot showing a red rectangular prism representing a standing tram. The x-axis ranges from -15 to 15, the y-axis from -1 to 1, and the z-axis from 0 to 4. The prism is centered at the origin (0,0,0) and has a height of 4 meters.</p>





560	Standing tram Hanover 1	
561	Standing tram Hanover 2	
562	Standing bicycle	

Table: library_DE_standard_traffic_signs

Description: The library of German standard traffic signs is based on the specifications of the Bundesanstalt für Straßenwesen (Status: 2019). For an assignment of the official number, see:

https://www.bast.de/BAST_2017/DE/Verkehrstechnik/Fachthemen/v1-verkehrszeichen/vz-download.html?nn=1817946

List of OBJTYPE:

OBJTYPE	Description / Official no.*	Pictogram
1001	101	
1002	101-10	
1003	101-11	
1004	101-12	
1005	101-13	
1006	101-14	
1007	101-15	
1008	101-20	
1009	101-21	
1010	101-22	


1011	101-23	
1012	101-24	
1013	101-25	
1014	101-51	
1015	101-52	
1016	101-53	
1017	101-54	
1018	101-55	
1019	102	
1020	103-10	
1021	103-20	
1022	105-10	
1023	105-20	
1024	108-4	

1025	108-5	
1026	108-6	
1027	108-7	
1028	108-8	
1029	108-9	
1030	108-10	
1031	108-11	
1032	108-12	
1033	108-13	
1034	108-14	
1035	108-15	
1036	108-16	
1037	108-17	
1038	108-18	





1039	108-19	
1040	108-20	
1041	108-21	
1042	108-22	
1043	108-23	
1044	108-24	
1045	108-25	
1046	110-4	
1047	110-5	
1048	110-6	
1049	110-7	
1050	110-8	
1051	110-9	
1052	110-10	



1053	110-11	
1054	110-12	
1055	110-13	
1056	110-14	
1057	110-15	
1058	110-16	
1059	110-17	
1060	110-18	
1061	110-19	
1062	110-20	
1063	110-21	
1064	110-22	
1065	110-23	
1066	110-24	



1067	110-25	
1068	112	
1069	114	
1070	117-10	
1071	117-20	
1072	120	
1073	121-10	
1074	121-20	
1075	123	
1076	124	
1077	125	
1078	131	
1079	133-10	
1080	133-20	



1081	136-10	
1082	136-20	
1083	138-10	
1084	138-20	
1085	142-10	
1086	142-20	
1087	145-10	
1088	150	
1089	151	
1090	153	
1091	156-10	
1092	156-11	
1093	156-20	
1094	156-21	




1095	157-10	
1096	157-11	
1097	157-20	
1098	157-21	
1099	159-10	
1100	159-11	
1101	159-20	
1102	159-21	
1103	162-10	
1104	162-11	
1105	162-20	
1106	162-21	

1107	201-50	
1108	201-51	
1109	201-52	
1110	201-53	
1111	205	
1112	206	

1113	208	
1114	209	
1115	209-10	
1116	209-30	
1117	211	
1118	211-10	
1119	214	
1120	214-10	
1121	214-30	
1122	215	
1123	220-10	
1124	220-20	
1125	220-40	


1126	222	
1127	222-10	
1128	223.1-50	
1129	223.1-51	
1130	223.1-52	
1131	223.2-50	
1132	223.2-51	
1133	223.2-52	
1134	223.3-50	
1135	223.3-51	
1136	223.3-52	



1137	224	
1138	224-40	
1139	224-41	
1140	224-51	
1141	229	
1142	229-10	
1143	229-11	
1144	229-20	
1145	229-21	
1146	229-30	
1147	229-31	
1148	237	

1149	238	
1150	239	
1151	240	
1152	241-30	
1153	241-31	
1154	242.1	
1155	242.1-40	
1156	242.2	
1157	244.1	
1158	244.1-40	
1159	244.2	
1160	245	
1161	250	
1162	251	

1163	253
1164	254
1165	255
1166	257-50
1167	257-51
1168	257-52
1169	257-53
1170	257-54
1171	257-55
1172	257-56
1173	257-57
1174	257-58
1175	259
1176	260

1177	261	
1178	262	
1179	263	
1180	264	
1181	265	
1182	266	
1183	267	
1184	268	
1185	269	
1186	270.1	
1187	270.1-40	
1188	270.2	




1189	272	
1190	273	
1191	274-5	
1192	274-10	
1193	274-20	
1194	274-30	
1195	274-40	
1196	274-50	
1197	274-60	
1198	274-70	
1199	274-80	
1200	274-90	
1201	274-100	
1202	274-110	

1203	274-120		
1204	274-130		
1205	274.1		
1206	274.1-20		
1207	274.1-40		
1208	274.1-41		
1209	274.2		
1210	274.2-20		
1211	275		
1212	276		
1213	277		
1214	278-5		
1215	278-10		
1216	278-20		

1217	278-30	
1218	278-40	
1219	278-50	
1220	278-60	
1221	278-70	
1222	278-80	
1223	278-90	
1224	278-100	
1225	278-110	
1226	278-120	
1227	278-130	
1228	279	
1229	280	
1230	281	

1231	282	
1232	283	
1233	283-10	
1234	283-11	
1235	283-20	
1236	283-21	
1237	283-30	
1238	283-31	
1239	286	
1240	286-10	
1241	286-11	
1242	286-20	
1243	286-21	
1244	286-30	





1245	286-31	
1246	290.1	
1247	290.1-40	
1248	290.2	
1249	301	
1250	306	
1251	307	
1252	308	

1253	310	
1254	310-40	
1255	311	
1256	314	
1257	314-10	
1258	314-20	
1259	314-30	
1260	314-50	
1261	314.1	
1262	314.1-40	
1263	314.2	
1264	315-50	
1265	315-51	
1266	315-52	

1267	315-53	
1268	315-55	
1269	315-56	
1270	315-57	
1271	315-58	
1272	315-60	
1273	315-61	
1274	315-62	
1275	315-63	
1276	315-65	
1277	315-66	
1278	315-67	
1279	315-68	
1280	315-70	


1281	315-71	
1282	315-72	
1283	315-73	
1284	315-75	
1285	315-76	
1286	315-77	
1287	315-78	
1288	315-80	
1289	315-81	
1290	315-82	
1291	315-83	
1292	315-85	
1293	315-86	
1294	315-87	





1295	315-88	
1296	316	
1297	316-50	
1298	317	
1299	318	
1300	325.1	
1301	325.1-40	
1302	325.2	
1303	327	





1304	327-50	
1305	327-51	
1306	328	
1307	330.1	
1308	330.2	
1309	331.1	
1310	331.2	
1311	333	
1312	333.1	
1313	333.1-20	





1314	350-10	
1315	350-20	
1316	350-40	
1317	354	
1318	356	
1319	357	
1320	357-50	
1321	357-51	
1322	357-52	





1323	358	
1324	363	
1325	365-50	
1326	365-51	
1327	365-52	
1328	365-53	
1329	365-54	
1330	365-55	
1331	365-56	
1332	365-57	
1333	365-58	
1334	365-59	
1335	365-60	
1336	365-61	

1337	365-62	
1338	365-63	
1339	365-64	
1340	365-65	
1341	365-66	
1342	365-67	
1343	365-68	
1344	390	
1345	390.2	
1346	391	
1347	392	
1348	393	

<p>1349</p>	<p>394</p>	 <p>A 3D plot showing a red cylinder. The vertical axis is labeled 'z [m]' with values 0 and 0.05. The horizontal axes are labeled 'x [m]' and 'y [m]' with values 0, -0.02, and 0.02. The cylinder is centered at the origin and extends from z=0 to z=0.05.</p>
<p>1350</p>	<p>394-50</p>	 <p>A 2D plot with 'x [m]' on the horizontal axis (range -0.5 to 0.5) and 'z [m]' on the vertical axis (range 0 to 1). A small red rectangle is centered at x=0, extending from approximately x=-0.05 to x=0.05 and from z=0 to z=0.05.</p>
<p>1351</p>	<p>401</p>	 <p>A 2D plot with 'x [m]' on the horizontal axis (range -0.5 to 0.5) and 'z [m]' on the vertical axis (range 0 to 1). A red rectangle is centered at x=0, extending from approximately x=-0.1 to x=0.1 and from z=0 to z=0.25.</p>
<p>1352</p>	<p>406-50</p>	 <p>A 2D plot with 'x [m]' on the horizontal axis (range -0.5 to 0.5) and 'z [m]' on the vertical axis (range 0 to 1). A red rectangle is centered at x=0, extending from approximately x=-0.1 to x=0.1 and from z=0 to z=0.65.</p>





1353	406-51	
1354	410	
1355	415-10	
1356	415-20	

<p>1357</p>	<p>415-40</p>	
<p>1358</p>	<p>418-10</p>	
<p>1359</p>	<p>418-20</p>	
<p>1360</p>	<p>418-40</p>	




1361	419-10	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the left, centered at z = 0.25. The arrow's tail is at x = 0.5 and its tip is at x = -0.5.</p>
1362	419-20	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the right, centered at z = 0.25. The arrow's tail is at x = -0.5 and its tip is at x = 0.5.</p>
1363	419-40	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the right, centered at z = 0.25. The arrow's tail is at x = -0.5 and its tip is at x = 0.5.</p>
1364	421-10	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the left, centered at z = 0.25. The arrow's tail is at x = 0.5 and its tip is at x = -0.5.</p>
1365	421-11	
1366	421-12	

1367	421-20	
1368	421-21	
1369	421-22	
1370	421-40	
1371	421-41	
1372	421-42	
1373	422-10	
1374	422-11	
1375	422-12	
1376	422-13	
1377	422-14	
1378	422-15	
1379	422-16	
1380	422-17	

1381	422-20	
1382	422-21	
1383	422-22	
1384	422-23	
1385	422-24	
1386	422-25	
1387	422-26	
1388	422-27	
1389	422-30	
1390	422-32	
1391	422-34	
1392	422-36	





1393	430-10	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the left, centered at z = 0.25. The arrow's tail is at x = 0.6 and its tip is at x = -0.5.</p>
1394	430-20	 <p>An empty 2D plot with x and z axes ranging from -1 to 1.</p>
1395	430-40	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the right, centered at z = 0.25. The arrow's tail is at x = -0.6 and its tip is at x = 0.6.</p>
1396	432-10	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the left, centered at z = 0.25. The arrow's tail is at x = 0.6 and its tip is at x = -0.5.</p>
1397	432-20	 <p>An empty 2D plot with x and z axes ranging from -1 to 1.</p>
1398	432-40	 <p>A 2D plot with x and z axes ranging from -1 to 1. A red arrow points to the right, centered at z = 0.25. The arrow's tail is at x = -0.6 and its tip is at x = 0.6.</p>

1399	442-10	
1400	442-11	
1401	442-12	
1402	442-13	
1403	442-20	
1404	442-21	
1405	442-22	
1406	442-23	
1407	442-50	
1408	442-51	
1409	442-52	
1410	442-53	

1411	448.1	
1412	450-50	
1413	450-51	
1414	450-52	
1415	450-53	
1416	450-54	
1417	450-55	
1418	454-10	

1419	454-20	
1420	454-40	
1421	455.1-10	
1422	455.1-11	
1423	455.1-12	
1424	455.1-20	
1425	455.1-21	
1426	455.1-22	
1427	455.1-30	
1428	455.1-50	
1429	455.2	

1430	457.1	
1431	457.2	
1432	458	
1433	460-10	
1434	460-11	
1435	460-12	
1436	460-20	
1437	460-21	
1438	460-22	
1439	460-30	
1440	460-50	

1441	466	
1442	467.1-10	
1443	467.1-20	
1444	467.1-30	
1445	467.2	
1446	501-10	
1447	501-11	
1448	501-12	
1449	501-13	
1450	501-14	

1451	501-15	
1452	501-16	
1453	501-17	
1454	501-18	
1455	501-20	
1456	501-21	
1457	501-22	
1458	501-23	
1459	501-24	
1460	501-25	
1461	501-26	
1462	501-27	
1463	501-28	
1464	505-11	

1465	505-12	
1466	505-21	
1467	505-22	
1468	511-10	
1469	511-11	
1470	511-12	
1471	511-20	
1472	511-21	
1473	511-22	
1474	511-25	
1475	511-26	
1476	513-10	
1477	513-11	
1478	513-20	





1479	513-21	
1480	514-10	
1481	514-20	
1482	515-11	
1483	515-12	
1484	515-21	
1485	515-22	
1486	521-30	
1487	521-31	
1488	521-32	
1489	521-33	
1490	522-30	
1491	522-31	
1492	522-32	





1493	522-33	
1494	522-34	
1495	522-35	
1496	522-36	
1497	522-37	
1498	522-38	
1499	523-30	
1500	523-31	
1501	524-30	
1502	524-31	
1503	524-32	
1504	524-33	
1505	525-31	
1506	526-31	





1507	526-33	
1508	531-10	
1509	531-11	
1510	531-12	
1511	531-13	
1512	531-20	
1513	531-21	
1514	531-22	
1515	531-23	
1516	532-10	
1517	532-20	
1518	532-21	
1519	533-20	
1520	533-21	





1521	533-22	
1522	535-11	
1523	535-21	
1524	536-20	
1525	536-21	
1526	537-30	
1527	537-31	
1528	541-10	
1529	541-11	
1530	541-20	
1531	541-21	
1532	542-10	
1533	542-11	
1534	545-11	





1535	546-10	
1536	546-11	
1537	550-20	
1538	550-21	
1539	550-22	
1540	550-23	
1541	550-24	
1542	551-20	
1543	551-21	
1544	551-22	
1545	551-23	
1546	551-24	





1547	590-10	
1548	590-11	
1549	600-30	
1550	600-31	
1551	600-32	





1552	600-33	
1553	600-34	
1554	600-35	
1555	600-36	





1556	600-37	
1557	600-38	
1558	600-39	
1559	600-60	





1560	605-10	
1561	605-11	
1562	605-12	
1563	605-13	
1564	605-14	
1565	605-20	
1566	605-21	





1567	605-22	
1568	605-23	
1569	605-24	
1570	605-40	
1571	605-41	
1572	605-42	
1573	605-43	
1574	605-44	
1575	605-45	

1576	610-40	
1577	610-41	
1578	610-42	
1579	610-43	


1580	615	
1581	616-30	
1582	616-31	
1583	620-40	

1584	620-41	
1585	625-10	
1586	625-11	
1587	625-12	

1588	625-13	
1589	625-20	
1590	625-21	
1591	625-22	

1592	625-23	
1593	626-10	
1594	626-20	
1595	626-30	
1596	626-31	
1597	626-32	

1598	628-10	
1599	628-11	
1600	628-20	
1601	628-21	
1602	628-40	
1603	628-41	
1604	628-42	
1605	628-43	
1606	629-10	
1607	629-11	
1608	629-20	
1609	629-21	
1610	629-40	
1611	629-41	

1612	629-42	
1613	629-43	
1614	630-10	
1615	630-20	
1616	720	